





# AX/VX Gasket Tool

The PSS Gasket Tool, handled and powered by an ROV, is designed to remove and install AX and VX wellhead gaskets. The tool is aligned with the gasket and lowered onto it. Hydraulic pressure is then used to expand the tool to the inner wall of the gasket. In the event of hydraulic failure after engagement, springs and small adjustable tabs located on the bottom of the tool secure the gasket.

## Features

- Failsafe Holding
- 3000 psi (210 Bar)
- 3000m Rated
- Light Weight



## 18-3/4" AX/VX Gasket

Part # TX00104-200-00

## 16-3/4" AX/VX Gasket

Part # TX00104-300-00

## 15" AX/VX Gasket

Part # TX00104-400-00

A001-350-086\_iss\_3

The specification details are illustrative for marketing purposes only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement.

The specification details are illustrative for marketing purposes only. Actual equipment may be different as a result of product improvement or other reasons. Specific interface and performance information should be reconfirmed at time of order placement.

---

[www.perryslingsbysystems.com](http://www.perryslingsbysystems.com)



**PERRY SLINGSBY SYSTEMS, LTD.**

 A MEMBER OF THE TRITON GROUP

**Houston | Aberdeen | Kirkbymoorside, UK | Singapore | Jupiter, FL, USA**