

C-SERIES ACTUATOR TO UU-CS/SS SERIES MOUNTING CHART

BALL VALVE	MAX BREAK	C-SERIES UNIT	BRACKET NUMBER	BOLTING HARDWARE	DRIVER NUMBER
1/4", 3/8", 1/2" UU-CS/SS	75 IN-LB	C-250(DA &SR)	CONTACT FACTORY	(4) M6 x 1.0P x 12MM w/Lockwashers PLUS (2) 1/4"-20UNCx1/2" w/Lockwashers	D-10
3/4" & 1" UU-CS/SS	150 IN-LB	C-250DA	B-4	DITTO	D-11
3/4" & 1" UU-CS/SS	150 IN-LB	C-450SR			D-12
1-1/4" UU-CS/SS	250 IN-LB	C-450DA	B-6	DITTO	D-14
1-1/4" UU-CS/SS	250 IN-LB	C-450SR	B-6		D-14
1-1/2" UU-CS/SS	350 IN-LB	C-450DA	B-6	DITTO	D-14
1-1/2" UU-CS/SS	350 IN-LB	C-1000SR	B-6	DITTO	D-15
2" UU-CS/SS (PTFE)	475 IN-LB	C-1000DA	B-6	DITTO	D-15
2" UU-CS/SS (PTFE)	475 IN-LB	C-1000SR	B-6	DITTO	D-15
2" UU-CS/SS (PEEK)	750 IN-LB	C-1000DA	B-6	DITTO	D-15
2" UU-CS/SS (PEEK)	750 IN-LB	C-2250SR	B-6	(4) M8 x 1.25P x 15MM w/Lockwashers PLUS (2) 1/4"-20UNCx1/2" w/Lockwashers	D-16