

Manipulator Mounted Saw

Cutters & Grinders.





DESCRIPTION

Using a 14" tungsten carbide saw blade the Manipulator Mounted Saw cuts through a multitude of materials with absolute ease and dexterity. Specially designed to mount on any manipulator wrist, using adaptor plates, the material to cut is simply grabbed with the manipulators jaws, held in place and cut.

Designed to fit to, rather than being held by the manipulator retains full function of the manipulators movements for further Subsea tasks without limitation. Once a material is located in position the blade is switched on and fed towards the material, on completion of a cut the blade retreats within the saws body protecting it and the manipulator from entanglement or obstruction and allows the next target to be located in moments.

FEATURES

Suitable for Cutting:

Anchor Chain

Wire Rope

Drill String

Various types of steel pipes

Cofl exip



Manipulator Mounted Saw

Cutters & Grinders.

SPECIFICATIONS

Working pressure Suitable for cutting 207 bar (3,000 psi), Anchor Chain

Wire Rope Drill String

Various types of steel pipes

Cofl exip

WHAT'S IN THE BOX

Manipulator Saw Adaptor plate

Tungsten carbide blade Operational hoses

Operations & Maintenance Manual.

PART NUMBERS & OPTIONS

SRTS-050

Manipulator Saw

www.f-e-t.com/subseatooling

Datasheet #A001-350-166 issue 3