

Serpent Series™ Flexible Hose Solution

As the pressure pumping industry evolves, Forum’s commitment to innovation continues with our 10,000 PSI and 15,000 PSI flexible hose solutions. Engineered for extreme conditions, our hoses incorporate several unique design features including a multi-color interior wear liner and modular end connections. These key attributes provide enhanced operating capabilities that contribute to superior reliability, improved efficiencies, and lower total cost of ownership.



Design Features

Benefits

100% Sourced and Manufactured in the USA	Superior Quality and Improved Availability
10K PSI Max Working Pressure / 15K PSI Test Pressure 15K PSI Max Working Pressure / 22.5K PSI Test Pressure	Meets Industry Standard Requirements
Bonded Construction Between Hose and Coupling	High Strength Connection Without Flow Restriction Points
Modular End Connections	Replaceable Ends Allows Easy Change Out of Connections
Multi-Color Interior Wear Liner	Simple Visual Indicator of Hose Condition
Protective Exterior Wrap and Bumpers	Protects Exterior of Hose During Operation and Transportation
Single-Strand Wire Construction	Smaller Minimum Bend Radius
Safety Restraint System	Ensures Maximum Safety During Operation

The Forum Serpent Series™ Allows for a Safer and More Reliable Wellsite, While Lowering Total Cost of Ownership

- Significant Reduction of End Connections
- Streamlines the Rig Up and Rig Down Process
- Eliminates the Recertification of Hundreds of High-Pressure Treating Iron Assets



Serpent Series™ Technical Details

Hose Series	Hose ID (in)	Working Pressure (psi)	Max Rate (bbl/min)	End Connection Options
Viper	2.5	10,000 15,000	18.2	3" XD Hammer Union 3" 1502 Hammer Union 2-9/16" 15K API 6A Flange or 16A Hub 3-1/16" 15K API 6A Flange or 16A Hub
Cobra	3.0	10,000 15,000	26.2	3" XD Hammer Union 3" 1502 Hammer Union 4" 1502 Hammer Union 3-1/16" 15K API 6A Flange or 16A Hub
Python	5.0	10,000 15,000	100.0	5-1/8" 10K API 6A Flange or 16A Hub 5-1/8" 15K API 6A Flange or 16A Hub
Anaconda	6.0	15,000	130.0	7-1/16" 15K API 6A Flange or 16A Hub

** 200' max length

** Additional end connection options can be applied per customer request