

Cable Specifications



GREASELESS ENVIRO-LITE E-LINE® CABLES

Cable Size	SIZE (in)	DIA (in)	B.S. lbs	WEIGHT (lbs/kft)	WEIGHT IN WATER (lbs/kft)	ARMOR WIRES IN/OUT	WIRES B.S. lbs IN/OUT	STRETCH COEFFICIENT ft/Kft/Klbs	CDR RESIS OHMS/Kft	CAP Pt/Ft	MAX TEMP °F	MIN SHEAVE DIA (in)	MAX VOLT
1-FT-350-11/12-HS-19-ETFJ-H	-	0.350	8500	169	126	11/6•6	537/370•292	1.50	2.8	56	375	26	1500
1-FT-350-11/12-HS-19-ETFJ	-	0.350	8500	164	121	11/12	537/292	1.65	2.8	56	375	26	1500

CONVENTIONAL WIRELINE CABLES

Cable Size	SIZE (in)	DIA (in)	B.S. lbs	WEIGHT (lbs/kft)	WEIGHT IN WATER (lbs/kft)	ARMOR WIRES IN/OUT	WIRES B.S. lbs IN/OUT	STRETCH COEFFICIENT ft/Kft/Klbs	CDR RESIS OHMS/Kft	CAP Pt/Ft	MAX TEMP °F	MIN SHEAVE DIA (in)	MAX VOLT
1-P-380-12/18-G-19	3/8	0.380	15000	259	218	12/18	585/585	1.00	2.8	39	300	21	1500
1-FT-380-12/18-G-19	3/8	0.380	15000	269	227	12/18	585/585	1.00	2.8	39	500	21	1500
1-P-322-12/18-G-19	5/16	0.322	11300	188	158	12/18	420/420	1.20	2.8	46	300	18	1500
1-FT-322-12/18-G-19	5/16	0.322	11300	193	163	12/18	420/420	1.20	2.8	48	500	18	1500
1-A-322-12/18-G-19	5/16	0.322	11300	196	166	12/18	420/420	1.20	2.8	45	550	18	1500
1-Q-322-12/18-G-19	5/16	0.322	11300	196	166	12/18	420/420	1.20	2.8	45	600	18	1500
1-FT-322-12/18-75-19	5/16	0.322	10400	197	168	12/18	387/387	1.20	3.3	48	500	18	1500
1-FT-322-12/18-77-19	5/16	0.322	10400	197	168	12/18	387/387	1.20	3.3	48	500	18	1500
1-FT-322-12/18-35N-19	5/16	0.322	11000	206	176	12/18	400/400	1.20	3.3	48	500	18	1500
1-P-288-12/18-G-19	9/32	0.288	10000	154	130	12/18	370/370	1.60	2.8	57	300	16	1500
1-T-288-12/18-G-19	9/32	0.288	10000	159	135	12/18	370/370	1.60	2.8	64	500	16	1500
1-FT-288-12/18-G-19	9/32	0.288	10000	157	134	12/18	370/370	1.60	2.8	55	500	16	1500
1-A-288-12/18-G-19	9/32	0.288	10000	159	135	12/18	370/370	1.60	2.8	54	550	16	1500
1-Q-288-12/18-G-19	9/32	0.288	10000	159	135	12/18	370/370	1.60	2.8	54	600	16	1500
1-FT-288-12/18-75-19	9/32	0.288	8200	158	135	12/18	308/308	1.90	4.0	49	500	16	1500
1-FT-288-12/18-77-19	9/32	0.288	8200	157	134	12/18	308/308	1.90	4.0	49	500	16	1500
1-FT-288-12/18-35N-19	9/32	0.288	9200	167	144	12/18	335/335	1.90	4.0	49	500	16	1500
1-P-258-12/18-G-19	1/4	0.258	7000	122	104	12/18	282/282	1.90	4.0	50	300	14	1200
1-T-258-12/18-G-19	1/4	0.258	7000	125	102	12/18	282/282	1.90	4.0	56	500	14	1200
1-FT-258-12/18-G-19	1/4	0.258	7000	126	103	12/18	282/282	1.90	4.0	51	500	14	1200
1-A-258-12/18-G-19	1/4	0.258	7000	126	104	12/18	282/282	1.90	4.0	48	550	14	1200
1-Q-258-12/18-G-19	1/4	0.258	7000	126	104	12/18	282/282	1.90	4.0	48	600	14	1200
1-FT-258-12/18-75-19	1/4	0.258	6000	127	108	12/18	247/247	2.30	4.4	51	500	14	1200
1-FT-258-12/18-77-19	1/4	0.258	6500	127	107	12/18	272/272	2.30	4.4	51	500	14	1200
1-FT-258-12/18-35N-19	1/4	0.258	6500	135	115	12/18	272/272	2.00	4.4	51	500	14	1200
1-P-224-12/18-G-19	7/32	0.224	5600	94	79	12/18	204/204	2.50	4.0	59	300	14	1200
1-T-224-12/18-G-19	7/32	0.224	5600	97	82	12/18	204/204	2.50	4.0	68	500	14	1200
1-FT-224-12/18-G-19	7/32	0.224	5600	97	82	12/18	204/204	2.50	4.0	61	500	14	1200
1-A-224-12/18-G-19	7/32	0.224	5600	99	84	12/18	204/204	2.50	4.0	58	550	14	1200
1-Q-224-12/18-G-19	7/32	0.224	5600	99	84	12/18	204/204	2.50	4.0	58	600	14	1200
1-FT-224-12/18-75-7	7/32	0.224	4800	96	81	12/18	186/186	2.90	6.7	45	500	14	1200
1-FT-224-12/18-77-7	7/32	0.224	5200	96	81	12/18	196/196	3.10	6.7	45	500	14	1200
1-FT-224-12/18-35N-7	7/32	0.224	5200	103	89	12/18	204/204	2.90	6.7	45	500	14	1200
1-P-224-15/15-G-19	7/32	0.224	5600	94	79	15/15	129/282	2.20	4.0	60	300	14	1200
1-T-224-15/15-G-19	7/32	0.224	5600	97	82	15/15	129/282	2.20	4.0	69	500	14	1200
1-FT-224-15/15-G-19	7/33	0.224	5600	97	82	15/15	129/282	2.20	4.0	58	500	14	1200
1-A-224-15/15-G-19	7/32	0.224	5600	99	84	15/15	129/282	2.20	4.0	58	550	14	1200
1-Q-224-15/15-G-19	7/32	0.224	5600	99	84	15/15	129/282	2.20	4.0	58	600	14	1200
1-FT-224-15/15-75-7	7/32	0.224	4800	93.0	80	15/15	115/247	2.70	6.7	44	500	14	1200
1-FT-224-15/15-77-7	7/32	0.224	5200	93.0	79	15/15	125/272	3.00	6.7	44	500	14	1200
1-FT-224-15/15-35N-7	7/32	0.224	5200	99.0	85	15/15	125/272	2.40	6.7	44	500	14	1200
1-P-185-12/15-G-7	3/16	0.185	3900	63	54	12/15	127/198	4.00	9.8	46	300	12	1000
1-T-185-12/15-G-7	3/16	0.185	3900	65	56	12/15	127/198	4.00	9.8	53	500	12	1000
1-A-185-12/15-G-7	3/16	0.185	3900	66	56	12/15	127/198	4.00	9.8	45	550	12	1000
1-Q-185-12/15-G-7	3/16	0.185	3900	66	56	12/15	127/198	4.00	9.8	45	600	12	1000
1-T-185-12/15-75-7	3/16	0.185	3500	65	56	12/15	111/171	4.50	10.9	53	500	12	1000